



UDF Series

Media Cartridges

Features

- 100% virgin materials - polypropylene or acrylonitrile styrene (AS)
- No talc or other chemicals added ensuring housings are sterile and hygienic
- No injection molding releasing agents used in manufacturing
- Patented lip seal with single recess top mounted O-ring design prevents pinching and leaks
- Side mounted O-ring groove for optional second O-ring
- Built-in pressure relief / air bleed button (optional)
- Various cap design and connection size options
- Compatible with multiple filter cartridge types
- Available in 10" standard (9-7/8" or 9-3/4")

Specifications

Material	O-ring: Buna-N Cap: 100% virgin polypropylene Sump: 100% virgin polypropylene / AS (clear)*
Connection	1/4", 3/8", 1/2", and 3/4"
Color	Various
Minimum temperature	4.4°C 40°F
Maximum temperature	40°C 104°F
Maximum pressure	Polypropylene: 8.6 bar 125 psi AS (clear): 6.9 bar 100 psi

*NSF certification listing not applicable for AS (clear) housings except for model H06-2C-WC



1/2", 3/4" connection cap (8 bolt hole design)

1/4", 3/8" connection cap (4 bolt hole design)

1/4", 3/8" connection cap (4 bolt hole design)



Optional pressure relief valve (PRV) (1/2" or 3/4" connection cap only)

Patented lip seal prevents leaks

Single recess mounted O-ring

20" Standard Series

Filter Housings



Features

- 100% virgin materials - polypropylene or acrylonitrile styrene (AS)
- No talc or other chemicals added ensuring housings are sterile and hygienic
- No injection molding releasing agents used in manufacturing
- Single recess top mounted O-ring design prevents O-ring pinching and leaks
- Side mounted O-ring groove for optional second O-ring
- Built-in pressure relief / air bleed button (optional)
- Equipped with filter cartridge centering plug to ensure zero bypass
- Available in 20" standard (9-7/8" or 9-3/4")

Specifications

Material	O-ring: Buna-N Cap: 100% virgin polypropylene Sump: 100% virgin polypropylene / AS (clear)*
Connection	3/8", 1/2", and 3/4"
Color	Various
Minimum temperature	4.4°C 40°F
Maximum temperature	40°C 104°F
Maximum pressure	Polypropylene: 8.6 bar 125 psi AS (clear): 6.9 bar 100 psi

*NSF certification listing not applicable for AS (clear) housings



Housing cap with pressure relief valve (PRV)



Housing cap mounting bolt hole



PRV protection plate (for protection during shipping)



Single recess mounted O-ring



Removable filter cartridge centering plug



10" Jumbo Series

Filter Housings

Features

- 100% virgin materials - polypropylene or acrylonitrile styrene (AS)
- No talc or other chemicals added ensuring housings are sterile and hygienic
- No injection molding releasing agents used in manufacturing
- Single recess top mounted O-ring design prevents O-ring pinching and leaks
- Side mounted O-ring groove for optional second O-ring
- Built-in pressure relief / air bleed button (optional)
- Equipped with filter cartridge centering plug to ensure zero bypass
- Supplied with standard cap mounting bolt kit
- Available in 10" standard (4.5" diameter)

Specifications

Material	O-ring: Buna-N Cap: 100% virgin polypropylene Sump: 100% virgin polypropylene / AS (clear)*
Connection	3/4", 1", 1-1/4", and 1-1/2"
Color	Various
Minimum temperature	4.4°C 40°F
Maximum temperature	40°C 104°F
Maximum pressure	Polypropylene: 6.9 bar 100 psi AS (clear): 6.9 bar 100 psi

*NSF certification listing not applicable for AS (clear) housings



Housing cap with pressure relief valve (PRV)



Housing cap mounting bolt hole



Optional 1" stainless steel connection



PRV protection plate (for protection during shipping)



Single recess mounted O-ring



Removable filter cartridge centering plug

20" Jumbo Series

Filter Housings



Features

- 100% virgin materials - polypropylene or acrylonitrile styrene (AS)
- No talc or other chemicals added ensuring housings are sterile and hygienic
- No injection molding releasing agents used in manufacturing
- Single recess top mounted O-ring design prevents O-ring pinching and leaks
- Side mounted O-ring groove for optional second O-ring
- Built-in pressure relief / air bleed button (optional)
- Equipped with filter cartridge centering plug to ensure zero bypass
- Supplied with standard cap mounting bolt kit
- Available in 20" standard (4.5" diameter)

Specifications

Material	O-ring: Buna-N Cap: 100% virgin polypropylene Sump: 100% virgin polypropylene / AS (clear)*
Connection	3/4", 1", 1-1/4", and 1-1/2"
Color	Various
Minimum temperature	4.4°C 40°F
Maximum temperature	40°C 104°F
Maximum pressure	Polypropylene: 6.9 bar 100 psi AS (clear): 6.9 bar 100 psi

*NSF certification listing not applicable for AS (clear) housings

